

# ALSPEC ALUMINIUM SYSTEMS

## TECHNICAL MANUAL

### KidScreen™ Window Fall Prevention

#### Section 4.0

#### CARE AND MAINTENANCE

---

##### PERIMETER FRAMING

Your new **KidScreen™ window fall prevention** “Product” has been manufactured using the highest quality materials available to the Architectural industry. Constructed from Architectural grade aluminum, these Products are highly corrosion resistant and exceptionally strong. With a moderate amount of maintenance as set out below, the Product will retain it's aesthetics and resist corrosion and rusting for years to come.

As a result of extensive research and testing, the Product is designed to resist corrosion and rusting, but as with all external elements on the building the Product requires some maintenance to keep it looking good and performing well. Depending on how harsh the environment elements are, the maintenance period will vary. Refer to recommended maintenance table below.

Your Product should only ever need to be washed down with a soft sponge using warm water and mild detergent. Rinse well with fresh water and remove any detergent residue. Strong detergents and abrasive cleaners should never be used to clean the **KidScreen™** as they may scratch or damage the surface finish.

##### SUGGESTED MAINTENANCE PERIOD TABLE

Environment	Recommended Maximum Maintenance Interval
Mild	Six Months
Moderate	Three Months
Tropical/Severe	One Month

##### Environmental Definitions:

**Mild** – Being rural, away from the coast and remote from industry and urban activity.

**Moderate** – Being mainly urban, inland and away from heavy industry.

**Tropical** – Being coastal/marine, subject to salt deposition and within 15km of the Eastern coast or 10km of the Western coast of Australia.